ALPINE® 2-T Synthetic

HC-synthetic two-stroke engine oil

Properties

- HC-synthetic two-stroke engine oil
- Good protection against rust, corrosion and wear
- Stable lubricating film prevents piston jamming and seizing
- Offers protection against deposits and plug bridging
- Use in systems with separate and mixed lubrication
- Environmentally friendly due to low smoke emission

Application notes

ALPINE 2-T Synthetic is a HC-synthetic two-stroke engine oil for air and water-cooled two-stroke engines in motor vehicles, motorcycles, scooters and mopeds with separate or mixed lubrication, up to a mixing ratio of 1:50.

Observe manufacturer‘s instructions.

Service description

Specifications:
- API TC
- ISO-L-EGD
- JASO FD
- TISI

Recommendations*:
- Husqvarna
- Piaggio Hexagon
- Rotax
- Stihl

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE 2-T Synthetic
Density at 15°C	DIN EN ISO 12185	kg/m³	858
Color	visually		green
Viscosity at 100°C	DIN ISO 51 562	mm²/s	7.5
Sulphated ash	DIN 51 575	% mass.	0.10
Pour point	ASTM D 7346	°C	-48
Flash point COC	DIN ISO 2592	°C	170

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

MITAN Mineralöl GmbH
Industriestr. 8 • 49577 Ankum • Tel.: 05462/747050 • Fax: 05462/747033
www.mitan-oil.de