

ALPINE® ZHF

HC-synthetic central hydraulic fluid

Properties

- Very high viscosity index
- Excellent wear protection
- Very low pour point
- No foam formation
- Very high thermal stability
- Reliable friction coefficient characteristics
- Excellent viscosity-temperature behaviour
- Excellent oxidation stability
- Neutral towards common sealing materials

Application notes

- Level control
- Shock absorber
- Hydropneumatic suspension
- Power steering
- Electrohydraulic soft top control
- Stability and traction systems
- Central locking

Observe manufacturer's instructions!

Service description

Recommendation*:

- Audi P/N G002000 & G002012
- Chrysler MS-1872 / MS-5931 / P/N 04883077 / MS-9602 / ATF+4 / MS10838 / P/N 05142893AA
- Ford M2C195-A / M2C204-A (extended temp. range)
- GM 9985010 / P/N 1052884 / GM 9985835 / P/N 12345866 (cold climate)
- Hyundai / Kia PSF-3, PSF-4
- MB 236.3 P/N 000 989 88 03
- MB 345.0 P/N 001 989 24 03
- Mitsubishi PS Fluid / Diamond SP II
- Nissan PSF-II
- Saab P/N (45) 30 09 800 & P/N 30 32 380
- Subaru P/N K0209A0080
- Toyota PSF Type EH, P/N 008886-01
- VW P/N G002000 & P/N G002012
- VW TL 521 46 (G00200 / G00400)
- Volvo P/N 1161529

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE ZHF
Thickness at 15°C	DIN 51 757	kg/m ³	856
Viscosity 40°C	DIN 51 562	mm ² /s	21.5
Viscosity 100°C	DIN 51 562	mm ² /s	6.5
Viscosity index (VI)	DIN ISO 2909	-	287
Pour point	DIN ISO 3016	°C	-51
Flash point COC	DIN ISO 2592	°C	>150
Colour		-	green

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.