

# ALPINE Fließfett EP 00/000

---

## Multi-purpose EP grease for central lubrication systems

### Properties

- Excellent adhesion on metal surfaces.
- Can be easily pumped, even at low temperatures.
- EP additives reduce wear and increase load resistance.
- Water resistant.
- Prevents corrosion.
- Mixable with most greases on conventional soap base.

### Use instructions

**Alpine Fließfett EP 00/000** is a semi-liquid fluid grease designed for use in central lubrication systems in commercial vehicles and stationary machines used in forestry, agriculture and construction.  
When re-lubricating parts, ensure that the grease is not contaminated with dust or dirt particles.  
Observe manufacturer instructions.

### Performance data

**Specifications:** DIN 51 502: GP 00/000 K-30

TYPICAL VALUES	METHOD	UNIT	ALPINE Fließfett EP 00/ 000
NLGI grade	ASTM D 217	-	00
Soap/thickener		-	lithium
Colour	visual	-	green
Texture	visual	-	smooth
Operating temperature range		°C	-50 to 120
Short term		°C	130
Penetration at 25°C	DIN ISO 2137	0.1 mm	400-430
Drop point	IP 396	°C	>160
Viscosity (base oil) at 40°C	ASTM D 7152	mm <sup>2</sup> /s	40
Flow pressure at -50°C	DIN 51805 mod	mBar	<1400

The above values may vary within commercially accepted tolerances

July 2016