

# ALPINE® ATF MB 17

## Low Viscosity HC-Synthetic Automatic Transmission Fluid

### Properties

- excellent fuel economy
- excellent lubricity
- very high thermal stability
- high, stable viscosity index
- very good oxidation stability
- Protection against wear, corrosion and foam formation
- excellent cooling capacity
- excellent frictional stability

### Application notes

- Especially for the latest Mercedes-Benz 9-speed automatic transmissions (9G-Tronic) 725.0 / 725.1 and 4MATIC
- **ALPINE ATF MB 17** also meets the specifications of MB 236.16.
- **ALPINE ATF MB 17 cannot** be used in older Mercedes-Benz automatic transmissions and is **not** downwards compatible with MB-Approval MB 236.10, MB 236.12, MB 236.14, MB 236.15

**Observe manufacturer's instructions!**

### Service description

#### Recommendation\*:

- MB 236.17

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE ATF MB 17
Thickness at 15°C	DIN EN ISO 12185	kg/m <sup>3</sup>	846.3
Viscosity 40°C	DIN 51 562	mm <sup>2</sup> /s	18.3
Viscosity 100°C	DIN 51 562	mm <sup>2</sup> /s	4.3
Viscosity index (VI)	DIN ISO 2909	-	150
Pour point	ASTM D 7346	°C	-54
Flash point COC	DIN ISO 2592	°C	184
Colour	-	-	yellow brown

August 2020

\* meets the requirements of the OEM manufacturer.  
The stated values may vary within the usual commercial range.