

ALPINE® Brake Fluid DOT 4

Brake fluid

Properties

- Synthetic fluid
- The very high dry and wet boiling point reduces vapour bubble formation
- Excellent protection of all metal parts of the brake system against corrosion
- Good protection against wear and foaming
- Seal compatible with all seals and hoses of the brake system

Application notes

ALPINE Brake Fluid DOT 4 is recommended for brake and clutch systems of vehicles for which a synthetic brake fluid according to DOT 4 is prescribed.

ALPINE Brake Fluid DOT 4 can be mixed with all synthetic brake fluids of the same quality.

Special notes:

- Store brake fluid only in its original sealed container.
- Brake fluid can cause damage to the vehicle paintwork.

Observe manufacturer's instructions!

Service description

Specifications:

- FMVSS 116 DOT 4
- SAE J 1703 / J 1704
- ISO 4925

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE Brake Fluid DOT 4
Density at 20°C	ASTM D4052	g/cm ³	1.06
Viscosity -40°C	SAE J1703 / 1704	mm ² /s	<1500
Dry boiling point (min.)	SAE J1703 / 1704	°C	>230
Wet boiling point (min.)	SAE J1703 / 1704	°C	>155

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.